



Single Phase Hybrid Inverter Datasheet

HYS-3000LV
HYS-3680LV
HYS-4600LV
HYS-5000LV
HYS-6000LV

Description

The HYS-LV Series is a high-performance single-phase hybrid inverter with excellent reliability, including power class from 3 kW to 6 kW.

The intelligent EMS function supports self-consumption mode, economic mode, and backup mode for multi-scenario applications.

Module-level monitoring management through Hoymiles Cloud allows users to remotely diagnose and track individual modules' performance over time, maximizing the total solar power production.

Features

01 Max. Efficiency 97.6%, European Efficiency 97.0%

02 Double MPPT tracker, up to 14A MPPT current

03 DC/AC ratio up to 150%

04 Ultralight for easy installation and space-saving

05 Support both DC-coupled and AC-coupled system

06 EMS integrates with self-consumption, economic mode, backup mode for multi-scenario applications

07 Built in dry contact flexibly set to earth fault alarm, load control or generator control

08 Remote monitoring through Hoymiles Cloud

Technical Specifications

Model	HYS-3000LV	HYS-3680LV	HYS-4600LV	HYS-5000LV	HYS-6000LV
Battery					
Battery Type	Li-ion / Lead-acid				
Rated Battery Voltage (V)	48				
Voltage Range (V)	40-60				
Max. Charge Current (A)	75	90	100	100	100
Max. Discharge Current (A)	75	90	100	100	100
Charging Strategy for Li-ion Battery	Self-adaption to BMS				
Charging Curve	3 Stages / Equalization				
External Temperature Sensor	Optional				
PV Input					
Max. PV Input Power (W)	4500	6000	7500	7500	7500
Max. PV Input Voltage (V)	550				
Nominal Input Voltage (V)	360				
MPPT Voltage Range (V)	125-500				
Start-up Voltage (V)	150				
Number of MPPTs	1	2	2	2	2
Max. Number of PV String per MPPT	1/1	1/1	1/1	1/1	1/1
Max. PV Input Current (A)	14/14	14/14	14/14	14/14	14/14
Short-circuit Current of PV Input (A)	17/17	17/17	17/17	17/17	17/17
AC Input and Output (On-grid)					
Nominal Output Apparent Power (VA)	3000	3680	4600	5000 ⁽¹⁾	6000 ⁽¹⁾
Max. Output Apparent Power (VA)	3000	3680	4600	5000 ⁽¹⁾	6000 ⁽¹⁾
Max. Input Apparent Power (VA)	6000	7360	7360	7360	7360
Nominal AC Voltage (V)	230				
Nominal Grid Frequency (Hz)	50/60				
Max. Output Current (A)	13.0	16.0	20.0	21.7	26.0 ⁽²⁾
Max. Input Current (A)	26.1	32.0	32.0	32.0	32.0
Power Factor	0.8 leading ... 0.8 lagging				
Total Harmonic Distortion (@ nominal output)	<3%				
AC Output (Off-grid)					
Max. Output Apparent Power (VA)	3000	3680	4600	5000	6000
Peak Output Apparent Power (VA) ⁽³⁾	6000, 10s	7360, 10s	9200, 10s	10000, 10s	10000, 10s
Nominal AC Voltage (V)	230				
Nominal AC Frequency (Hz)	50/60				
Max. Output Current (A)	13.0	16.0	20.0	21.7	26.0
Total Harmonic Distortion (@ linear load)	<3%				

Technical Specifications

Model	HYS-3000LV	HYS-3680LV	HYS-4600LV	HYS-5000LV	HYS-6000LV
Efficiency					
Max. Efficiency	97.6%	97.6%	97.6%	97.6%	97.6%
Euro Efficiency	97.0%	97.0%	97.0%	97.0%	97.0%
Max. Battery to Load Efficiency	95.0%	95.0%	95.0%	95.0%	95.0%
MPPT Efficiency	99.9%	99.9%	99.9%	99.9%	99.9%
Protection					
Anti-islanding Protection	Integrated				
PV String Input Reverse Polarity Protection	Integrated				
Insulation Resistor Detection	Integrated				
Residual Current Monitoring Unit	Integrated				
AC Over Current Protection	Integrated				
AC Short Current Protection	Integrated				
AC Over-voltage and Under-voltage Protection	Integrated				
Surge Protection	DC Type II / AC Type III				
General					
Dimension (W × H × D) [mm]	502 × 461 × 202				
Weight (kg)	25				
Mounting	Wall Mounting				
Operation Temperature (°C)	-25 to +65 (>45, derating)				
Relative Humidity	0-95%, no condensing				
Altitude (m)	≤4000				
Cooling	Natural convection				
Protection Degree	IP65				
Noise (dB [A])	<40				
User Interface	LED & APP				
Communication with BMS	RS485, CAN				
Communication with Meter	RS485				
Communication Interface	RS485, Wi-Fi/WLAN/GPRS (optional)				
Digital Input/output	DRM, 1 × DI, 2 × DO				
Isolation Method (Solar/Battery)	Transformerless / High-frequency Isolation				
Certifications and Standards					
Grid Regulation	EN 50549, VDE-AR-N 4105, AS/NZS 4777.2				
Safety Regulation	IEC 62109-1, IEC 62109-2				
EMC	EN 61000-6-1, EN 61000-6-3				

(1) 4600 for VDE-AR-N 4105 & VDE0126-1-1; 4999 for AS/NZS 4777.2

(2) 21.7A for AS/NZS 4777.2

(3) Can be achieved only if PV and battery power are sufficient